

#### **INVITATION TO BID**

#### THE HOUSING AUTHORITY OF THE CITY OF BAYONNE 549 AVENUE A, BAYONNE, N.J. 07002

The Housing Authority of the City of Bayonne is receiving bids for **PURCHASING OF LIGHTING FIXTURES.** 

The Housing Authority of the City of Bayonne, the Awarding Authority (the "Owner"), will receive sealed bids no later than **NOVEMBER 13**, 2025 AT 11:30 AM, prevailing time at the office of the Housing Authority of the City of Bayonne, at the address set forth above, 549 Avenue A, Bayonne, NJ 07002 in order to be considered.

Parties interested in submitting a Sealed Bid may retrieve detailed Specifications from the Authority's website at <a href="www.bayonneha.org/bids">www.bayonneha.org/bids</a> beginning on October 29, 2025. Any questions can be directed to <a href="mailto:epacyna@bayonneha.org">epacyna@bayonneha.org</a>.

Bids must be submitted in a sealed envelope, addressed to the Authority, as directed by the Specifications. Envelopes shall contain, on the exterior, the designation of the contract for which the bid is entered, and the name, address and telephone number of the Bidder.

Parties choosing to submit their bids via the United States mail are required to have the mail delivered prior to the appointed bid opening time. Proper consideration must be given to allow for weekends and holidays.

The Authority reserves the right to waive any informality in any bid or bids, to reject any and all bids, and to accept such bid or bids and to make such awards as may be in the best interest of the Authority.

The Invitation for Bid and the contract awarded to it comply with the fair and open process, established and further defined by N.J.S.A. 19:44A-20.7. Consequently, the provision of N.J.S.A 19:44A-20.5 and N.J.S.A 19:44A-20.26, as to campaign contributions, do not apply to the Invitation to Bid and the contract to be awarded hereunder.

Bidders and the successful Contractor and his subcontractors will be required to comply with Affirmative Action Regulations of the State of New Jersey, stipulated in N.J.S.A. 10:5-31-38, and to comply with Chapter 33 of the Public Laws of 1977 and with the requirements of Public Law of 1975, Chapter 127, and N.J.A.C. 17:27 "Law Against Discrimination", current regulations, as well as all federal Affirmative Action Programs.

All Bidders, including corporations, partnerships, and sole proprietorships, must submit a Statement of Ownership.

The project is being executed with funds provided by the U.S. Government through Department of Housing and Urban Development.

John T. Mahon, Executive Director Housing Authority of the City of Bayonne

### SPECIFICATIONS FOR PURCHASING OF LIGHTING FIXTURES BID HOUSING AUTHORITY OF THE CITY OF BAYONNE

#### **SCOPE**

The Housing Authority of the City of Bayonne (the "Authority") is seeking bids for the below listed ceiling tiles or equivalents. The Authority is seeking to purchase suspended ceiling tiles.

#### **DESCRIPTION**

- 800 x Lithonia Lighting Catalog Number TRUW 48 AL026 CMP 8SWW2 ZT MVOLT (**OR EQUIVALENT**). See attachment #1.
- 65 x Lithonia Lighting Catalog Number MNSS L96 AL03 MVOLT SWW3 (**OR EQUIVALENT**). See attachment #2.

#### REQUIREMENTS OF THE VENDOR

The Vendor must be a franchised and/or authorized factory representative, able to furnish the specified lighting fixtures. Dealers or agents submitting a Quote may be required to submit a letter of certification from the manufacturer whose product is proposed, certifying that they are authorized by the manufacturer to supply the lighting fixtures specified. The Authority reserves the right to request such certification and to require that such certification be delivered within five (5) working days from the time it is requested. The Vendor must notify the Authority of any changes in the status of its franchise.

- The lighting fixtures supplied must be standard manufacturer's product line, available to the general public.
  - A Vendor shall provide new lighting fixtures only. Used lighting fixtures are not acceptable.
- This Bid Solicitation is for the outright purchase of the lighting fixtures only.
- All bids should be submitted with complete detailed specifications of the lighting fixtures.
- Bids shall include and state manufactures warranty.
- Bids shall include destination and delivery charges.
- Bids shall include an estimated delivery date.

#### **DELIVERY**

Bids shall include an estimated delivery date.

The Vendor must supply the following at the time of delivery:

1. Manufacturer's Certificate of Origin

**IMPORTANT NOTE:** Each lighting fixture and any components shall be completely assembled, serviced and ready for use when delivered. Unless specified otherwise; any parts, components, equipment, controls, materials, features, performances, capacities, ratings or designs which are standard and/or necessary to form an efficient and complete working lighting fixtures shall be furnished whether specifically required herein or not. The Vendor shall supply any item not specified herein but deemed necessary for the intended use and the item must meet the Industry standards and practices, Federal and New Jersey Safety Standards and Regulations, and SAE and other applicable standards.

The manufacturer's standard warranty must be supplied with each lighting fixture at the time of delivery and shall be in typed form. The warranty commences with the acceptance of the vehicle at the delivery site and following the final inspection.

The Vendor must provide complete information on warranty coverage.

#### **COST**

TOTAL LUMP SUM

ATTACH BREAKDOWN OF COSTS FOR INDIVIDUAL LIGHTING FIXTURES.

| ALL LIGHTING FIXTURES                       | \$43, 311.35                      |
|---|-----------------------------------|
|   |                                   |
| IKIO LED LIGHTING LLC                       | 46-4700072                        |
| Company Name                                | Federal ID # or Social Security # |
| 8470 Allison Pointe Blvd, Suite 128 Indiana | apolis, IN 46250                  |
| Address                                     | Inderpreet Singh                  |
| Signature of Authorized Agent               | Type or Print Name                |
| Business Development Manager                |                                   |
| Title                                       |                                   |
| +1 317-737-4287                             | 11.11.2025                        |
| Telephone Number                            | Date                              |
|   |                                   |
| NIL   | isingh@ikioledlighting.com        |
| Fax Number                                  | E-mail address                    |



### **COST BREAKDOWN**

#### <u>Itemized pricing for fixtures, warranty, and any optional features.</u>

Below is a Cost breakdown proposal for the full scope of work described in the RFP, including all materials, Freight, administrative support, and warranties. IKIO LED Lighting, certifies that these costs are reasonable, necessary, and fixed — no additional or hidden charges will apply.

Delivery of the lighting fixtures is 15-20 days from the date of receipt.

#### ITEMIZED COST BREAKDOWN

| COST CATEGORY                | UNIT COST (USD) | QUANTITY | SUBTOTAL<br>(USD) |
|------------------------------|-----------------|----------|-------------------|
| Oriled Wraparound Light (4') | \$46.99         | 800      | \$37,592.00       |
| Apex Linear Low Bay (8')     | \$87.99         | 65       | \$5,719.35        |
| Freight                      |                 | Included | \$0.00            |
| Total                        |                 |          | \$43,311.35       |





ITEM SKU#: 662187512945

# Oriled

## Wraparound Light (4')

INDUSTRIAL LIGHTING | WRAPAROUND LIGHTS

#### **FEATURES**

- High-efficiency output of 151lm/W reducing energy consumption without compromising brightness.
- Control flexibility with DC sensors and 0-10V dimming systems provides adaptive, efficient lighting that responds to real-time conditions.
- Optional emergency battery backup available to maintain illumination during power outages.
- Multiple mounting options, including surface mount and suspension kits, deliver versatile solutions for installation.

#### **APPLICATION AREAS**

Workspaces, Educational Facilities, Offices & Commercial Interiors, Hospitals & Clinics, Warehouses & Industrial Spaces, Parking Garages & Corridors, Cold Storage & Utility Areas

#### PRODUCT DETAILS

#### **ELECTRICAL**

| Max Power                       | 39.89W                  |
|---------------------------------|-------------------------|
| Voltage                         | 120-277V                |
| Current                         | 0.08A-0.10A-0.14A-0.16A |
| Power Factor                    | 0.97                    |
| Total Harmonic Distortion (THD) | 8.2%                    |

#### LIGHTING PERFORMANCE

| Lumens                         | 3360lm-3926lm-5134lm-6360lm   |
|--------------------------------|-------------------------------|
| Efficacy                       | 151lm/W                       |
| Color Temperature (Selectable) | 3000K-3500K-4000K-5000K-6500K |
| Color Rendering Index (CRI)    | 81                            |
| R9 (Red Value)                 | 2                             |
| R13 (Skin Tones)               | 83                            |
| Beam Angle                     | 105°                          |
| Dimmable Lighting Control      | 0-10V Dimming                 |

#### Note:

\*Mentioned lumen output is calculated as such: 3360.8lm at 21W, 3926.7lm at 26W, 5134lm at 34W, 6360lm at 39.89W

#### **ENVIRONMENT**

| Operating Temperature | -4°F ~ +122°F |  |
|-----------------------|---------------|--|
| Suitable Location     | DAMP          |  |
| LIFESPAN              |               |  |
| Average Life (Hours)  | 50,000        |  |
| Warranty (Years)      | 5             |  |

#### COMPONENTS

| LED Light Source | SEOUL STW8A2PD                  |
|------------------|---------------------------------|
| Driver           | Simon - SIF30 SIF40 SIF50 SIF60 |

#### CONSTRUCTION

| Housing        | Steel Sheet |  |
|----------------|-------------|--|
| Cover Material | PMMA        |  |
| Diffuser       | Frosted     |  |
| Power Supply   | Hard Wired  |  |
| Finish         | White       |  |

#### **PART NUMBER & QUALIFICATIONS**

| Ordering Part Number  | IK-WL04-21/26/34/40W-MV-5CCT-DY |
|-----------------------|---------------------------------|
| Qualified Part Number | IK-WL04-21/26/34/40W-MV-5CCT-DY |
| SKU Number            | 662187512945                    |







Not all product variations listed on this page are DLC qualified. Visit https://www.designlights.org/qpl to confirm qualification.

### Oriled Wraparound Light (4')



#### **DIMENSIONS AND WEIGHT**

| Length (Inches)  | 47.7" |  |
|------------------|-------|--|
| Width (Inches)   | 7.1"  |  |
| Height (Inches)  | 2.8"  |  |
| Net Weight (lbs) | 5.51  |  |



#### **PACKAGING**

| Box Dimensions (Inches) | 48.58" x 7.32" x 2.99" |
|-------------------------|------------------------|
| Box Weight (lbs)        | 27.51                  |
| Quantity Per Box        | 4                      |

#### **SUPPORTING DOCUMENTS**

| DOCUMENTS                 | DOCUMENT LINK   |
|---------------------------|-----------------|
| IES Files                 | View / Download |
| LM79 Report               | View / Download |
| LM80 Report               | View / Download |
| Installation Instructions | View / Download |

#### **ORDERING INFORMATION**

| SKU NUMBER   | DESCRIPTION  | QUANTITY/BOX |
|--------------|--|--------------|
| 662187512945 | ORILED WRAPAROUND LIGHT (4'): 39.89W / 3360-3926-5134-6360LM / 30-35-40-50-65K / WHITE | 4            |



ITEM SKU#: 662187482781

# Apex Linear Low Bay (8')

COMMERCIAL LIGHTING | LINEAR LOW BAYS

#### **FEATURES**

- Increased flexibility and ease with IKIO's CCT & Power Selectable feature.
- High Efficacy Lighting with 80+ CRI, resulting in crisp, uniform, and flicker-free illumination of the space.
- Ensured Longevity with rugged iron housing, an effective heat sink, and durable polycarbonate lens.
- 0-10V Seamless Dimming Function, allowing adjustment of the brightness of light.
- Easy-to-Install Design that supports quick screw-in during installations, making lighting upgrades hassle-free.

#### **APPLICATIONS**

Parking Lots, Garages, Warehouses, Workshops & Production Areas, Walkways, Restaurants, Retail Stores

#### **MOUNTING OPTIONS**

- Surface Mounting
- · Pendant Mounting (Kit Sold Separately)

#### **PRODUCT DETAILS**

#### ELECTRICAL

| Max Power                              | 72.4W    |
|--|----------|
| Voltage                                | 120-277V |
| Current                                | 0.29A    |
| Power Factor                           | 0.9      |
| Total Harmonic Distortion (THD)        | 15%      |
| Surge Protection L/N-PE: 2kV, L-N: 1kV |          |

#### LIGHTING PERFORMANCE

| Lumens   | 6993.5lm-8392.2lm-10123lm                          |  |
|--|--|--|
| Efficacy 139.87lm/W                              |  |  |
| Color Temperature (Selectable) 3000K-4000K-5000K |  |  |
| Color Rendering (CRI) 84                         |  |  |
| R9 (Red Value)                                   | 11   |  |
| R13 (Skin Tones) 85-87-83                        |  |  |
| Beam Angle 130°                                  |  |  |
| Light Distribution Type I, Very Short            |  |  |
| Dimmable Lighting Control                        | ighting Control Continuous Dimming to 10% or Below |  |

#### Note:

\*Mentioned lumen output is calculated as such: 6993.5lm at 50W, 8392.2lm at 60W and 10123lm at 72.4W

\*Mentioned R13 value is calculated @70W.



#### **ENVIRONMENT**

| Operating Temperature          | -31°F ~ +113°F |  |
|--------------------------------|----------------|--|
| Suitable Location              | DAMP           |  |
| Ingress Protection Rating (IP) | IPX4           |  |

#### **LIFESPAN**

| Average Life (Hours) | 50,000                        |
|----------------------|-------------------------------|
| Warranty (Years)     | 7 (Extendable Up to 10 Years) |

#### COMPONENTS

| LED Light Source | Lumileds SMD2835              |  |
|------------------|-------------------------------|--|
| Driver           | Becky - BQE65-1250-52-PV-S1S2 |  |

#### CONSTRUCTION

| Housing Iron          |                       |  |
|-----------------------|-----------------------|--|
| Cover Material / Lens | Polycarbonate (Round) |  |
| Diffuser              | Frosted               |  |
| Finish White          |                       |  |

#### **PART NUMBER & QUALIFICATIONS**

| Ordering Part Number  | IK-LLB08-70W-30/40/50K-MV-WH  IK-LLB08-70W-30/40/50K-MV-[BR, WH BL, GR,SL]-[MP,DM or blank] |  |
|-----------------------|---|--|
| Qualified Part Number |   |  |
| SKU Number            | 662187482781  |  |







Not all product variations listed on this page are DLC qualified. Visit https://www.designlights.org/qpl to confirm qualification.




### Apex Linear Low Bay (8')



#### **DIMENSIONS AND WEIGHT**

| Length (Inches)  | 96.06" |  |
|------------------|--------|--|
| Width (Inches)   | 2.97"  |  |
| Height (Inches)  | 3.24"  |  |
| Net Weight (lbs) | 7.27   |  |

| PACKAGING  Box Dimensions (Inches) | 97.63" x 10.62" x 8.26" |  |
|------------------------------------|-------------------------|--|
| Box Weight (lbs)                   | 40.78                   |  |
| Quantity Per Box                   | 6                       |  |



#### SUPPORTING DOCUMENTS

| DOCUMENTS                 | DOCUMENT LINK   |
|---------------------------|-----------------|
| Product Sheet             | View / Download |
| IES Files                 | View / Download |
| LM79 Report               | View / Download |
| LM80 Report               | View / Download |
| Installation Instructions | View / Download |

#### **ORDERING INFORMATION**

| SKU NUMBER   | DESCRIPTION   | QUANTITY/BOX |
|--------------|---|--------------|
| 662187482781 | APEX LLB: 8FT / 72.4W / 6993.5-8392.2-10123LM / 30-40-50K / 120-277V / WHITE / WITHOUT SENSOR | 6            |

#### **ACCESSORIES**

#### **INCLUDED IN THE BOX**

| SKU NUMBER   | PRODUCT CODE | DESCRIPTION       | DOCUMENT LINK   |
|--------------|--------------|-------------------|-----------------|
| 662187482828 | IK-LLB08-SMK | SURFACE MOUNT KIT | View / Download |

NOTE: Surface mounting kit is inside the fixture.

#### SOLD SEPARATELY

| SKU NUMBER   | PRODUCT CODE  | DESCRIPTION          | DOCUMENT LINK   |
|--------------|---------------|----------------------|-----------------|
| 662187482811 | IK-LLB-LP     | LINKABLE PLATE       | View / Download |
| 662187482842 | IK-LLB08-ARC  | SUSPENSION CABLE KIT | View / Download |
| 662187482835 | IK-ACC-8W-EMD | EMERGENCY LED DRIVER | View / Download |
| 662187482828 | IK-LLB08-SMK  | SURFACE MOUNT KIT    | View / Download |

NOTE: Other Options on Request/Customized: Finish (BR-Bronze, BL-Black, GR-Gray, SL-Silver, MP-AC PIR Sensor, DM- DC Motion Sensor)

